

ORGANIC 40

Product Data

PREMIUM SBS MODIFIED BASE SHEET

Organic 40 is manufactured from superior quality organic felt that is saturated with asphalt and then coated on both sides with weathering grade SBS Modified asphalt and then covered on top with mineral surface fines to prevent sticking in the roll.

Certifications

Manufactured to comply with:

ASTM D2626 - 04

Installation

ORGANIC 40 base sheet can be used for commercial as well as residential roofing system. **ORGANIC 40** base sheet is applied over the flat roofing deck or insulation before the application of Build-Up Roofing systems. Follow building code and local amendments when installing **ORGANIC 40**. Refer to the Tile Roofing Institute (TRI) manual when used as a clay or concrete tile underlayment.



**Manufactured in the USA
Producing American Jobs!**

Technical Data

Typical Properties, 2.0 square roll

- Average Weight of roll = 78.0 lbs
- Mass of Asphalt Saturant = 7.2 lbs / 100 ft sq
- Mass of desaturated felt = 5.2 lbs / 100 ft sq
- Saturation efficiency (min) by weight = 70%
- Breaking Strength at 77F (min)
- Machine direction = 35 lbf/in
- Cross Direction = 20 lbf/in
- No. of Rolls per Pallet = 25

Width: 36 Inches
Coverage: 216 Sq. Ft
Packaging: 25 Rolls Per Pallet
25 Pallets Per Truckload

Warranty

GMC offers a 15 year limited material warranty on single ply and 30 year limited material warranty on double ply to approved applicators. Please contact GMC Roofing & Building Paper Products representative for full details.



Manufactured by
GMC Roofing & Building Paper Products, INC.
6400 Zerker Road, Shafter, CA. 93263
(661) 399 4324
www.gmcpaper.com